

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 753 583 A1

(12)

EUROPEAN PATENT APPLICATION

published in accordance with Art. 158(3) EPC

(43) Date of publication:
15.01.1997 Bulletin 1997/03

(51) Int. Cl.⁶: **C12Q 1/60, C12Q 1/44,
C12Q 1/26**

(21) Application number: 95913411.5

(86) International application number:
PCT/JP95/00641

(22) Date of filing: 03.04.1995

(87) International publication number:
WO 96/23902 (08.08.1996 Gazette 1996/36)

(84) Designated Contracting States:
**AT BE CH DE DK ES FR GB GR IE IT LI LU MC NL
PT SE**

(30) Priority: 31.01.1995 JP 13607/95

(71) Applicant: **DAIICHI PURE CHEMICALS CO. LTD.**
Chuo-ku Tokyo103 (JP)

(72) Inventors:
• **HINO, Koichi;**
Daiichi Pure Chemicals Co., Ltd.
Tokyo 130 (JP)

• **NAKAMURA, Mitsuhiro**
Daiichi Pure Chemicals Co.,
Sumida-ku Tokyo 130 (JP)
• **MANABE, Mitsuhsa**
Daiichi Pure Chemicals Co.,
Sumida-ku Tokyo 130 (JP)

(74) Representative: **Wächtershäuser, Günter, Prof.**
Dr.
Patentanwalt,
Tal 29
80331 München (DE)

(54) METHOD OF QUANTITATIVE ANALYSIS OF CHOLESTEROL

(57) A method for quantitatively determining cholesterol in high density lipoproteins, in which, prior to the determination of cholesterol by an enzymatic method, a surfactant and a substance which forms a complex with lipoproteins other than high density lipoproteins are added to a sample containing lipoproteins.

The method does not require any pretreatments such as centrifugal separation. With a simple operation, cholesterol in HDLs can be measured effectively. Also, this method can be adopted in a variety of automated analyzers, and thus is very useful in the field of clinical assays.

EP 0 753 583 A1

Description**Technical Field**

5 The present invention relates to a method for measuring cholesterol in high-density lipoproteins, eliminating the necessity of pretreatments such as centrifugal separation and effectively providing simple analytical method while requiring only small amounts of a sample.

Background Art:

10 Serum lipids such as cholesterol are bound to apoproteins and form lipoproteins. Lipoproteins are categorized into chylomicrons, very low-density lipoproteins, low-density lipoproteins (LDLs), and high-density lipoproteins (HDLs) based on differences in physical properties. Among these lipoproteins, LDLs are known to be atherogenic, and HDLs are known to have anti-atherogenic action.

15 As it has been proven epidemiologically that the cholesterol level in HDLs inversely correlates to the frequency of onset of arteriosclerotic diseases, measurement of cholesterol in HDLs is quite common today for the purposes of predicting and diagnosing ischemic diseases.

Several methods are known to measure HDL cholesterol. In one method, for example, cholesterol is measured after separating HDLs from other lipoproteins using an ultracentrifugation. In another method, lipids are stained after they are isolated by electrophoresis, and the strength of color development is measured. However, these methods all involve problems such as intricate procedures, inability to handle many samples, etc., and therefore, they have not been used routinely in clinical laboratories.

20 The most widely used method for measuring cholesterol in HDLs in clinical laboratories is a precipitation method. In this method, a precipitant is added to a sample to aggregate lipoproteins other than HDLs, the aggregated lipoproteins are precipitated by centrifugation, and cholesterol present in a supernatant containing only HDLs is measured.

Although this method is simpler than ultracentrifugation or electrophoresis, not all the analyzing steps can be completely automated. Since it involves a separation operation using a centrifugation. Manual processes for obtaining a supernatant containing only HDL in this method increases the risk of causing analytical error and demand a relatively great amount of sample when compared to other automated clinical tests.

30 On the other hand, methods using enzymes to fractionally determine cholesterol in HDLs are studied. For example, a method in which enzymatic reaction is carried out in the presence of a bile acid salt or a nonionic surfactant is known (Japanese Patent Application Laid-open (kokai) No. 63-126,498). This method is based on the finding that the enzymatic reaction rate in the initial stage of reaction is in proportion to LDL concentration, and thereafter, to the concentration of cholesterol in HDLs. This method cannot be said to be precise, since enzymatic reaction with cholesterol in HDLs cannot be completely separated from that with other lipoproteins. In other words, cholesterol subject to the enzymatic reaction shifts from cholesterol in LDLs to that in HDLs, not in steps manner but in a gradual manner involving partial overlap.

40 According to another known method, lipoproteins other than HDLs are aggregated in advance, and only the cholesterol in HDLs is enzymatically reacted. Thereafter, enzymes are inactivated, and the aggregated lipoprotein is simultaneously re-dissolved to measure absorption (Japanese Patent Application Laid-open (kokai) No. 6-242,110). This method requires addition of reagent at least three times. Therefore, it can be applied to limited autoanalyzers only, raising a drawback regarding range of use. In addition, in re-dissolving the precipitation, use of a high concentration salt is needed. Therefore, this method is not satisfactory from not only the view point of damage to the analytical apparatus, but also of difficulty in disposing the waste reagent.

45 Accordingly, an object of the present invention is to provide a method for quantitatively determining cholesterol in high-density lipoproteins which eliminates the necessity of pretreatments such as centrifugal separation, which effectively provides simple mensuration, and which can be applied to a variety of automated analyzers.

Under the afore-mentioned circumstances, the present inventors have conducted careful studies, and have found that cholesterol in HDLs can be quantitatively determined efficiently using automated analyzers if a sample is subjected to enzymatic mensuration of cholesterol after it is mixed with a surfactant and with a substance which forms a complex with lipoproteins other than HDLs, leading to completion of the invention.

Disclosure of the Invention

55 The present invention relates to a method for quantitatively determining cholesterol in high density lipoproteins, characterized in that, mensuration of cholesterol in a sample is performed after a surfactant and a substance which forms a complex with lipoproteins other than HDLs are added to the sample.

Best Mode for Carrying Out the Invention

The substance which forms a complex with lipoproteins other than HDLs used in the present invention can be any substance insofar as its affinity to HDLs is different from that to lipoproteins other than HDLs. Examples of such substances include polyanions such as dextrin sulfate, phosphotungstic acid, and heparin; divalent metal ions such as magnesium ions and calcium ions; water-soluble polymers such as polyethylene glycol; and antibodies to lipoproteins other than HDLs. They can be used singly or in combinations of two or more. Among the possibilities, a combination of a polyanion and a divalent metal ion is preferred.

The amounts of these substances to be used are not particularly limited, and differ depending on the kinds of substances. It suffices that these substances form complexes together with lipoproteins other than HDLs at the time of measurement. Coagulation may or may not occur. For example, when a polyanion and a divalent metal ion are used in combination, it is preferred that the concentration of polyanion be 0.02 to 2 % by weight, and that of the divalent metal ion be 10 to 500 mM, after they are admixed with the sample. Particularly preferred is the case where concentration of polyanion is 0.05 to 1% by weight and that of divalent metal ion is 20 to 200 mM.

The surfactant used in the present invention preferably has the inhibitory effect on the interaction between the enzymes used for the detection of cholesterol and lipoproteins, or in other words, the surfactant preferably does not dissolve lipoproteins. Examples of such surfactants include polyoxyethylene alkylethers, polyoxyethylene alkylphenylethers, polyoxyethylene - polyoxypropylene condensation products, polyoxyethylene alkylether sulfates, and alkyl benzene sulfonates. Preferable examples of polyoxyethylene alkylethers include polyoxyethylene cetyl ether (HLB 14) (as commercial products, there are Emulgen 220 manufactured by Kao Corp., etc.). Preferable examples of polyoxyethylene alkylphenylethers include polyoxyethylene nonylphenylether (HLB 15) (as commercial products, there are Emulgen 913 manufactured by Kao Corp., etc.). Preferable examples of polyoxyethylene - polyoxypropylene condensation products include commercially available Pluronic F88 manufactured by Asahi Denka K.K. Preferable examples of polyoxyethylene alkylether sulfates include sodium polyoxyethylene lauryl ether sulfate (as commercial products, there are Emal 20C manufactured by Kao Corp., etc.). Preferable examples of alkyl benzene sulfonates include sodium dodecyl benzene sulfonates.

These surfactants may be used singly or in combinations of two or more. Although their amounts are not particularly limited, that are preferably used in such amounts that concentration after being mixed with a sample is from 0.01 to 5% by weight, particularly preferably from 0.05 to 1% by weight.

In the present invention, a surfactant and a substance which forms a complex with lipoproteins other than HDLs are first added to a sample. The two materials may be added as one reagent after being blended, or they may be added as two separate reagents.

Next, the sample to which has been added a surfactant and a substance which forms a complex with lipoproteins other than HDLs is subjected to a direct determination of cholesterol. That is, no pretreatment such as centrifugation is required.

Any known enzymatic method may be used for measuring cholesterol. For example, cholesterol esterase and cholesterol oxydase may be combined and used as enzyme reagents. Alternatively, cholesterol esterase and cholesterol dehydrogenase may be combined. Among enzymatic methods, methods employing a combination of cholesterol esterase and cholesterol oxidase are preferred.

After adding an enzyme, the amount of signals within a certain period of time is measured, thereby determining the concentration of cholesterol. In order to enhance the accuracy of analysis, signal amounts between two fixed points of time after addition of enzyme may be compared (2 point method). For the calibration purpose, a sample with known HDL value is analyzed similarly.

The method for determining cholesterol in the final stage following addition of enzyme reagent, etc., is not particularly limited. For example, an absorption analysis in which peroxidase and a chromogen are combined may be used as well as methods detecting coenzymes or hydrogen peroxide.

Examples:

The present invention will next be described by way of example, which should not be construed as limiting the present invention.

Example 1:

Using serum samples Nos. 1 to 10 containing lipoproteins, cholesterol in HDLs was determined by the present invention and by a conventional precipitation method, and the obtained data were compared. The results are shown in Table 1.

Briefly, 4 μ l of a sample was combined with 300 μ l of a reagent containing 0.2% of phosphotungstic acid, 100 mM of magnesium chloride, and 0.5% of a polyoxyethylene - polyoxypropylene condensate (Pluronic F-68, manufactured

by Asahi Denka K.K.). Then, 100 μ l of a cholesterol mensuration reagent containing 0.2 U/ml of cholesterol esterase, 0.2 U/ml of cholesterol oxydase, 0.3 U/ml of peroxydase, 0.04% of N,N-dimethylmetatoluidine, 0.05% of 4-aminoantipyrine, and 0.1% Triton X-100 was added. Subsequently, the change in absorption at 545 nm was monitored, obtaining the concentration of cholesterol in HDLs by comparing the change in absorption with that given with a sample having assigned HDL value. The above operation was performed using a Hitachi model 7150 autoanalyzer.

In determining cholesterol in HDLs independently using a precipitation method, 0.2 ml of an aqueous solution containing 0.3% of dextran sulfate and 2% of magnesium chloride was mixed with 0.2 ml of a sample. The mixture was centrifugally separated at 3,000 rpm for 10 minutes. 50 μ l of a supernatant was collected and mixed with 3 ml of a cholesterol mensuration reagent prepared as described above, followed by incubation at 37°C for 10 minutes. Absorption at 545 nm was measured to obtain the concentration of cholesterol in HDLs.

Table 1

Sample No.	Concentration of cholesterol (mg/dl)	
	invention method	precipitation method
1	79	80
2	65	64
3	64	64
4	64	58
5	15	18
6	81	88
7	47	48
8	38	38
9	47	46
10	33	32

From the results in Table 1, it is understood that although the method of the present invention is simple, the values obtained were comparable to those obtained by the conventional method.

Example 2:

Using samples Nos. 11 to 20 containing lipoproteins, cholesterol in HDLs was determined by the present invention and by a conventional precipitation method, and the obtained data were compared. The results are shown in Table 2.

Briefly, 4 μ l of a sample was combined with 300 μ l of a reagent containing 0.2% of phosphotungstic acid, 1.8 g/l of dextran sulfate, 100 mM of magnesium chloride, and 0.2% of a polyoxyethylene - polyoxypropylene condensate (Pluronic F-68, manufactured by Asahi Denka K.K.). Then, 100 μ l of a cholesterol mensuration reagent same as that used in Example 1 was added. Thereafter, by a method similar to that in Example 1, the concentration of cholesterol in HDLs was obtained.

Separately, a precipitation method was performed as described in Example 1.

Table 2

Sample No.	Concentration of cholesterol (mg/dl)	
	invention method	precipitation method
11	47	45
12	38	34
13	36	32
14	54	52
15	26	22
16	93	92
17	61	62
18	36	32
19	55	50
20	75	74

From the results in Table 2, it is understood that although the method of the present invention is simple and requires only a small amount of sample, the values obtained were comparable to those obtained by the conventional method.

Industrial Applicability

According to the present invention, cholesterol in HDLs can be effectively determined by a simple method. It does not require any pretreatments such as centrifugal separation. Also, since this method provides specific measurement with a small amount of sample and simple operation, it can be adopted in a variety of automated analyzers. Thus, the method is very useful in the field of clinical assays.

Claims

1. A method for quantitatively determining cholesterol in high density lipoproteins characterized in that, prior to the determination of cholesterol by an enzymatic method, a surfactant and a substance which forms a complex with lipoproteins other than high density lipoproteins are added to a sample containing lipoproteins.
2. The method for quantitatively determining cholesterol in high density lipoproteins according to Claim 1, wherein a surfactant and a sample to which a substance which forms a complex with lipoproteins other than HDLs have been added is directly subjected to determination of cholesterol.
3. The method for quantitatively determining cholesterol in high density lipoproteins according to Claim 1 or 2, wherein the substance which forms a complex with lipoproteins other than HDLs is a polyanion, a divalent metal ion, a water-soluble polymer, or an antibody to lipoproteins other than high density lipoproteins.
4. The method for quantitatively determining cholesterol in high density lipoproteins according to any one of Claims 1 through 3, wherein the surfactant does not dissolve lipoproteins.
5. The method for quantitatively determining cholesterol in high density lipoproteins according to any one of Claims 1 through 4, wherein cholesterol is determined by a method in which cholesterol esterase and cholesterol oxydase are used in combination.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/JP95/00641

A. CLASSIFICATION OF SUBJECT MATTER		
Int. Cl ⁶ C12Q1/60, 44, 26		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
Int. Cl ⁶ C12Q1/60, 44, 26		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP, 6-242110, A (Kokusai Shiyaku K.K.), September 2, 1994 (02. 09. 94) (Family: none)	1 - 5
A	JP, 63-126498, A (Boehringer Mannheim GmbH.), May 30, 1988 (30. 05. 88) & EP, 265933, A & DE, 880511, A	1 - 5
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "T" document published prior to the international filing date but later than the priority date claimed "I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "Z" document member of the same patent family		
Date of the actual completion of the international search June 2, 1995 (02. 06. 95)		Date of mailing of the international search report June 20, 1995 (20. 06. 95)
Name and mailing address of the ISA/ Japanese Patent Office Facsimile No.		Authorized officer Telephone No.

Form PCT/ISA/210 (second sheet) (July 1992)